



DATA TABLE

SIZE	BSP	C (mm)	W (mm)	WEIGHT (g)
1/2"	1/2"	112.5	51.2	177
3/4"	3/4"	130.2	65.5	300
1"	1"	142.5	73.7	450
1 1/4"	1 1/4"	161.0	86.6	680
1 1/2"	1 1/2"	166.5	102.0	950
2"	2"	214.0	120.0	1610
2 1/2"	2 1/2"	228.0	135.0	3400
3"	3"	269.0	188.0	3900
4"	4"	309.0	216.0	6200

MATERIALS TABLE

PART	MATERIAL
Stem	PVC
Handle	ABS
Stem O-Ring	EPDM
Union Nut	PVC
End Connector	PVC
Body O-Ring	EPDM
O-Ring	EPDM
Body	PVC
Ball	PVC
Seat Seal	PTFE
Seat Carrier	PVC
Carrier O-Ring	EPDM

SPECS

- WRAS Approved
- Maximum Working Pressure - 10bar
- Operation Temperature 0 - 60°C

RELATED PRODUCTS

- [51023 - 500ml Griffon Uni-100 PVC Cement](#)
- [51010 - 500ml Tangit Cement](#)
- [51024 - 500ml Griffon WDF-05 Fast Setting PVC Cement](#)
- [51021 - 500ml Griffon Pipe Cleaner](#)
- [2817 - 50mm roll Emery Cloth](#)
- [40911 - Centre Pull Paper Towel](#)

Temperature Derating Table

Temperature C	Pressure rating bar
20	10.0
30	8.0
40	5.8
50	3.9
60	2.2

Plastic Pipe Shop Ltd

Unit 1, Craig Leith Road
Broadleys Business Park,
Stirling, FK7 7XQ
Web: www.plasticpipeshop.co.uk
Email: sales@plasticpipeshop.co.uk
Tel: 01786 472 850

Plastic Pipe Shop Ltd

Drawing Name	Imperial Threaded Double Union Ball Valve
Drawing No.	IMPBSPDUBV/ERC58
Drawn by	BB
Last revision	14 February 2019
Sheet	1/1
Manufacturer	ERA