



DATA TABLE

SIZE	B (mm)	C (mm)	D (mm)	PCD (mm)	HOLES	Recommended Bolt Size	Weight (g)
1/2"	21.4	95.0	16.0	65.0	4	M12	78
3/4"	26.7	105.0	19.0	75.0	4	M12	105
1"	33.6	115.0	22.0	85.0	4	M12	143
1 1/4"	42.2	140.0	27.0	100.0	4	M16	220
1 1/2"	48.3	150.0	32.0	110.0	4	M16	280
2"	60.3	165.0	38.0	125.0	4	M16	300
2 1/2"	75.2	185.0	44.0	146.0	4	M16	505
3"	88.9	203.0	51.0	160.0	8	M16	685
4"	114.3	220.0	62.0	180.0	8	M16	940

SPECS

- WRAS Approved
- Maximum Working Pressure - 16bar
- Operating Temperature 0 - 60°C

RELATED PRODUCTS

- [51023 - 500ml Griffon Uni-100 PVC Cement](#)
- [51010 - 500ml Tangit Cement](#)
- [51024 - 500ml Griffon WDF-05 Fast Setting PVC Cement](#)
- [51021 - 500ml Griffon Pipe Cleaner](#)
- [2817 - 50mm roll Emery Cloth](#)
- [40911 - Centre Pull Paper Towel](#)

Temperature Derating Table

Temperature C	Pressure rating bar
20	16.0
30	12.8
40	9.3
50	6.2
60	3.5

Plastic Pipe Shop Ltd

Unit 1, Craig Leith Road,  
Broadleys Business Park,  
Stirling, FK7 7LQ  
Web: [www.plasticpipeshop.co.uk](http://www.plasticpipeshop.co.uk)  
Email: [sales@plasticpipeshop.co.uk](mailto:sales@plasticpipeshop.co.uk)  
Tel: 01786 472 850

Plastic Pipe Shop Ltd

Drawing Name	Imperial Full Face Flange PN10
Drawing No.	IMPFFFFPN10/PPF14
Drawn by	BB
Last revision	21 June 2019
Sheet	1/1
Manufacturer	EFFAST/PLIMAT