



**DATA TABLE**

SIZE	B (mm)	C (mm)	D (mm)	L (mm)	W (mm)	WEIGHT (g)
20mm	20	78.0	51.0	16.0	50.0	177.0
25mm	25	90.0	58.0	19.0	60.0	304.0
32mm	32	104.0	65.0	22.0	68.0	460.0
40mm	40	120.0	76.0	26.0	80.0	690.0
50mm	50	140.0	88.0	31.0	94.0	960.0
63mm	63	169.0	104.0	38.0	115.0	1610.0
75mm	75	227.0	138.0	44.0	168.0	2200.0
90mm	90	242.0	138.0	51.0	168.0	5200.0
110mm	110	282.0	166.0	61.0	210.0	7300.0

**SPECS**

- WRAS Approved
- Maximum Working Pressure:
  - 16bar (16-63mm)
  - 10bar (75-110mm)
- Operation Temperature 0 - 60°C

**RELATED PRODUCTS**

- 51125 - 125ml UNI100 Griffon Cement w.brush
- 51023 - 500ml UNI100 Griffon Cement w. brush
- 51025 - 500ml UNI100 Griffon Cement - Tin
- 51012 - 500ml Tangit Cement - Tin
- 51024 - 500ml WDF-05 Blue Fast Setting Cement
- 51021 - 500ml PVC Cleaner
- 2817 - 50mm roll Emery Cloth
- 40911 - Centre Pull Paper Towel

**Temperature Derating Table (16bar)**

Temperature C	Pressure rating bar
20	16.0
30	12.8
40	9.3
50	6.2
60	3.5

**Temperature Derating Table (10bar)**

Temperature C	Pressure rating bar
20	10.0
30	8.0
40	5.8
50	3.9
60	2.2

**Plastic Pipe Shop Ltd**

Unit 1, Craig Leith Road  
 Broadleys Business Park,  
 Stirling, FK7 7XQ  
 Web: [www.plasticpipeshop.co.uk](http://www.plasticpipeshop.co.uk)  
 Email: [sales@plasticpipeshop.co.uk](mailto:sales@plasticpipeshop.co.uk)  
 Tel: 01786 472 850

**Plastic Pipe Shop Ltd**

Drawing Name	Metric Industrial Double Union Ball Valve EPDM
Drawing No.	METINDDUBVEPDM/PPF114
Drawn by	BB
Last revision	10 September 2019
Sheet	1/1
Manufacturer	EFFAST